

The Hustler FasTrak™ Specifications

Model	16/44	18/44	18/52	20/52
Engine	OHV, Honda	OHV, Honda	OHV, Honda	OHV, Honda
Horsepower	16	18	18	20
No. of Cylinders	2	2	2	2
Displacement	32.3 cu in (614cc)	37.5 cu in (614cc)	37.5 cu in (614cc)	37.5 cu in (614cc)
Compression Ratio	8:1	8.3:1	8.3:1	8.3:1
Max. Torque	31.7 ft lbs @ 2500 rpm	31.8 ft lbs @ 2500 rpm	31.8 ft lbs @ 2500 rpm	32.5 ft lbs @ 2500 rpm

ELECTRICAL SYSTEM

12 volt, 15 amp regulated

Ignition Electronic

Fuel Capacity 12.2 US gal (46.18 L)

TRANSMISSION

Dual hydrostatic, Hydro-Gear IZT

Forward Speeds 0-7 mph (0-11.26 kph), infinitely variable

Reverse Speeds 0-5 mph (0-8 kph), infinitely variable

Steering Twin lever, true zero degree turning radius



BRAKES

Service Hydrostatic dynamic braking

Parking Sprocket and cog. Patent-pending integral park brake system (when steering levers are placed in off position, park brakes are automatically engaged).

SEAT

Adjustable, deluxe high back. Optional armrests.

TIRES

Front Casters	11 x 4-5, rib thread	11 x 4-5, rib thread	11 x 4-5, rib thread	11 x 4-5, rib thread
Rear Drive	18 x 8.50-8, turf tread	18 x 8.50-8, turf tread	18 x 9.50-8, turf tread	18 x 9.50-8, turf tread

MOWER

Side Discharge	44 in	44 in	52 in	52 in
Width	44 in (111.76 cm)	44 in (111.76 cm)	52 in (132.08 cm)	52 in (132.08 cm)
Blades	3, 15.7 in x 2.5 in x .20 in	3, 15.7 in x 2.5 in x .20 in	3, 18.3 in x 2.5 in x .20 in	3, 18.3 in x 2.5 in x .20 in
Cutting Height	1-4 in	1-4 in	1-4 in	1-4 in

DIMENSION

Model	16/44	18/44	18/52	20/52
Height	38 in (96.52 cm)	38 in (96.52 cm)	38 in (96.52 cm)	38 in (96.52 cm)
Length	65 in (165.10 cm)	65 in (165.10 cm)	69.62 in (176.83 cm)	69.62 in (176.83 cm)
Width Overall	49.2 in (124.97 cm)	49.2 in (124.97 cm)	57.2 in (145.29 cm)	57.2 in (145.29 cm)
Net Weight	730 lbs (3311.21 kg)	730 lbs (3311.21 kg)	740 lbs (3356.57 kg)	740 lbs (3356.57 kg)

WARRANTY

A full two-year warranty (limited warranty for commercial use)

A lifetime warranty on the leading edge of the mowing deck